

Colouring of Plans

Building (Administration) Regulation 14(3) requires that one copy of every plan submitted for approval shall be coloured in order to clearly differentiate existing work from proposed new work and one part of any proposed new work from other parts.

2. For consistency in the use of colour, AP/RSE/RGE are advised to adopt BS 5252:1976, “Framework for colour co-ordination for building purposes” as the standard and the preferred colours are as shown in Appendix A.

3. BS 5252F “Colour matching fan” contains 64 mm square patches of all the colours in the BS 5252 framework and should be used in conjunction with the colour cards produced by drawing material manufacturers in order to select the best possible match within their range of products.

4. For amendments to the approved works, authorized persons (AP)/registered structural engineers (RSE)/registered geotechnical engineers (RGE) are strongly requested to colour or otherwise identify the proposed works from the approved works, with identical colouring or other means, on **all** sets of plans submitted to the Buildings Department to facilitate the vetting of the plans.

5. The use of these recommended colours and the differentiation of proposed works from existing/approved works on all sets of amendment plans will expedite the processing of plans and is therefore clearly in the interests of all parties.

(CHEUNG Hau-wai)
Building Authority

Ref. : GP/BREG/A/14

First issue March 1988

Last revision January 1990

This revision August 2006 (AD/NB1) (General Revision)

Index under : B(A)R 14(3) - Colouring of Plans
Colouring of Plans - B(A)R 14(3)

Preferred Colours

Material	Preferred Colour	BS 5252 Identification Code
Earth (unexcavated)	Fawn	06 C 33
Hardcord or dry fill	Brown	06 C 39
Brick	Red	04 E 55
Concrete (plain or reinforced)	Green	14 E 53
Solid Concrete Blocks	Blue	20 E 56
Hollow Concrete Blocks	Mauve	24 E 53
Lightweight Partition (e.g. Plasterboard)	Orange	06 E 55
Plaster or Cement Rendering	Magnolia	08 E 49
Mosaic or other non-absorbent floor tiles	Pink	02 C 33
Mosaic or other non-absorbent wall tiles	Lemon	10 E 50
Glass	Blue	20 E 50
Timber doors	Brown	06 D 44
Metalwork	Grey	00 A 03
Steel	Purple	24 C 39
Sanitary fittings	Yellow	10 E 55
Provision for the disabled e.g. toilets, lifts, ramps	Green	12 E 53

Notes :

1. Ducts, light-wells and lift shafts should be left uncoloured.
2. For elevations and the larger plan areas, colouring may be in lighter washes of the preferred colours in order to avoid a garish effect e.g. concreted, tiled or plastered areas.
3. A light colour wash should be used to identify phased development.
4. A colour legend or key should be added to all sets of drawings.