

2 Embedded water supply pipes* - flow meter test



Turn off all water taps

Record the reading on the water meter
and repeat again after 30 minutes

Check any change in the second reading to
verify if there is leakage in the water supply pipes

3 Embedded water supply pipes* - reversible pressure test

Record the number of water dripping at prominent
seepage spot on the ceiling for about 30 minutes

Turn off water supply mains

Turn on all taps to drain off water and release
pressure within the water supply pipes

Record the number of water dripping at the
selected spot again for 30 minutes

Observe if the dripping rate slows down to verify
if there is leakage at the water supply pipes

Turn on the water supply mains and turn off all taps

Record the number of water dripping at the same selected spot again for
30 minutes to reconfirm if there is leakage at the water supply pipes

*It is advisable to engage a licensed plumber to conduct a comprehensive inspection of the water supply system, and to decide the appropriate investigation method such as use of pressurised equipment for testing.

Public Health and Municipal Services (Amendment) Ordinance 2025

Under the Public Health and Municipal Services Ordinance (Chapter 132), if the source of water seepage posing a sanitary nuisance is identified, the authorized public officers will issue a "Nuisance Notice" and may also apply to the Court for a "Nuisance Order" to the person causing the nuisance, requiring the abatement of the nuisance within a specified period. With effect from 17 August 2025, a person who fails to comply with a "Nuisance Notice" is liable to a fine of \$25,000 and a daily fine of \$450, while a person who fails to comply with a "Nuisance Order" is liable a fine of \$50,000 and a daily fine of \$600. In addition, public officers may enter premises between 7 a.m. and 10 p.m. to investigate nuisance. Any person who, without reasonable excuse, fails to comply with a Notice of Intended Entry shall be guilty of an offence and liable to a fine of \$5,000.



Learn more about the (Amendment) Ordinance

Consider consulting a building professional for assistance if the source of seepage cannot be identified.

Joint Office of Buildings Department and Food and Environmental Hygiene Department

www.bd.gov.hk / www.fehd.gov.hk

For enquiries, please call 1823



Owners have the responsibility to properly manage and maintain their buildings. If water seepage occurs, owners should investigate the source of seepage by liaising with owners/occupiers of the flat concerned for carrying out repair works as early as possible.

**Co-operate with neighbours
to stop water seepage**

Water Seepage Investigation

DIY Guideline

1 Observe and record



1 seepage location (ceiling, wall)



2 timing of occurrence (continuous, intermittent or after raining)



3 seriousness of dampness, odour and colour



4 any defective drainage pipe at external wall

2 Common sources and signs of seepage at ceiling

1 Defective drainage pipes embedded in floor slab of upper flat

- seepage area below kitchen, toilet or bathroom
- intermittent seepage with circular shape seepage area
- mouldy seepage area with stinky smell

2 Defective water - proofing of floor slab of upper flat

- seepage area below bathroom
- seepage area below surface channel or shower area
- relatively large seepage area with even dampness, or seepage area near walls

3 Leaking water supply pipe embedded in floor slab of upper flat

- water dripping at seepage area
- greyish crystalline deposit at seepage area, indicating presence of salt water

3 Simple Testing Methods

1 Drainage and water proofing of slab - colour water and ponding tests

- inexpensive and effective
- food dye to be used on health and safety considerations
- colour water may stain the ceiling/wall
- different colour dyes for identification of different testing locations



Dilute colour dye with about 10 liters of water



Fill basin and water storage tank of watercloset with colour water and then discharge the colour water

Wet the junction between floor drain and concrete slab with colour water and then pour colour water into the outlet



Splash all junctions of the walls of the shower area and curbs with colour water for a while and then discharge colour water into the outlet

Splash the wall sealant of the bathtub with colour water for a while and then discharge colour water into the outlet and overflow outlet (check connexion of overflow outlet)

Plug the floor drain and cover the floor with a shallow colour water pond^ for 1 hour and then unplug the outlet

Plug the outlet of the shower area, splash junctions with walls and curbs, cover the shower area with a shallow colour water pond for 1 hour, and then unplug the outlet

Observe the seepage area to see any sign of colour water seepage as it may take 1 hour to 2 weeks for colour water to seep through and appear on the ceiling



^ Install temporary precautionary measures such as water bags for surrounding furniture, electrical appliances, etc.